

# KENCO ENGINEERING COMPANY

P.O. BOX 470426 TULSA, OK 74147-0426

PHONE: (918) 663-4406 FAX: (918) 663-4480

[www.kenco-eng.com](http://www.kenco-eng.com) e-mail: [info@kenco-eng.com](mailto:info@kenco-eng.com)

## REPAIR KITS FOR 8800

### **GAUGE GLASS REPAIR KIT MODEL #**

8800-RK-(CL)-(O-RING SEAL MATERIAL)-(SIGHT TUBE OPTION)- (SS, CS or PVC)

#### **GLASS REPAIR KITS- CONSIST OF THE FOLLOWING:**

- (1) 5/8" O.D. SIGHT TUBE
- (2) SIGHT TUBE O-RING SEALS
- (X) SIGHT TUBE ISOLATORS (QUANTITY BASED ON LENGTH)

CL = CENTER TO CENTER DIMENSION IN INCHES (EXAMPLE: 0.000)

#### **O-RING SEAL MATERIAL OPTIONS**

V = FLUOROCARBON  
A = AFLAS  
B = BUNA-N  
E = ETHYLENE PROPYLENE  
T = FEP ENCAPSULATED SILICONE

#### **STANDARD SIGHT TUBE OPTIONS**

GS = 5/8" O.D. STANDARD GAUGE GLASS  
HP = 5/8" O.D. HIGH PRESSURE GAUGE GLASS  
HW = 5/8" O.D. HEAVY WALL GAUGE GLASS  
RL = 5/8" O.D. TRUE REDLINE GAUGE GLASS  
GSRL = 5/8" O.D. STANDARD GAUGE GLASS WITH REDLINE ADHESIVE TAPE (SUITABLE FOR APPLICATION TEMPERATURES UP TO 212°F / 100°C)  
HPRL = 5/8" O.D. HIGH PRESSURE GAUGE GLASS WITH REDLINE ADHESIVE TAPE (SUITABLE FOR APPLICATION TEMPERATURES UP TO 212°F / 100°C)  
HWRL = 5/8" O.D. HEAVY WALL GAUGE GLASS WITH REDLINE ADHESIVE TAPE (SUITABLE FOR APPLICATION TEMPERATURES UP TO 212°F / 100°C)

### **SHIELD REPAIR KIT MODEL #**

8800-(CL)-(SHIELD STYLE)- (SS, CS or PVC)

CL = CENTER TO CENTER DIMENSION IN INCHES (EXAMPLE: 0.000)

#### **SHIELD STYLES:**

L = CLEAR POLYCARBONATE  
H = HEIGHT SCALE  
RH = RATE SCALE & HEIGHT SCALE  
MRH = METRIC RATE HEIGHT SCALE  
MH = METRIC HEIGHT SCALE  
M = EXPANDED METAL